

RS-53 (R470A)

New non-flammable low GWP Drop-in replacement for R-410A



GWP (Global Warming Potential) of 979

1/5 For more information visit: www.lowgwpref.com / www.replacementforr22.com / service@comstarproducts.com 1-800-328-0142 / www.comstarproducts.com / ComStar International Inc. New York, USA

RS-53 INTRODUCTION

RS-53 (R470A) is a new non-flammable Drop-in replacement for R-410A with a low Global Warming Potential (GWP) less than half that of R-410A. RS-53 (R470A) has a similar thermodynamic performance to R-410A with matching energy efficiency and cooling capacity. RS-53 (R470A) is compatible with the materials commonly found in R-410A equipment. In particular, RS-53 (R470A) contains low toxicity components already known to have excellent chemical stability in air-conditioning units.

RS-53 (R470A) is an exciting new development in the quest to replace higher GWP refrigerants in both existing and new equipment. RS-53 (R470A) enables users to replace R-410A in existing units with minimal changes and inconvenience at low cost. RS-53 (R470A) is compatible with lubricants typically used with R-410A avoiding the need to change the existing lubricant when retrofitting. RS-53 (R470A) is thus an excellent option to replace R-410A, not only in the European Union where F Gas regulations are creating shortages, but also in other countries which are introducing restrictions on the sale and use of refrigerants containing hydrofluorocarbons.

R32 is being introduced as a replacement for R-410A in new equipment, but is not suitable for use in existing equipment because it is flammable. In contrast, RS-53 (R470A) is a retrofit solution being non-flammable, low toxicity and with similar cooling capacity, pressures and Coefficient of Performance to R-410A.

GLOBAL WARMING POTENTIAL



PERFORMANCE CHARACTERISTICS

- Low direct GWP Drop-in replacement for R-410A
- Similar energy efficiency to R-410A
- Close match for R-410A in cooling capacity
- Similar discharge pressure to R-410A
- No changes to hardware required during retrofitting
- Compatible with lubricants commonly used with R-410A

- Replaces R-410A in air conditioning and refrigeration applications
- Similar Flow Rate to R-410A
- Zero Ozone Depletion Potential
- Non-flammable & low toxicity

For more information visit: www.lowgwpref.com / www.replacementforr22.com / service@comstarproducts.com 1-800-328-0142 / www.comstarproducts.com / ComStar International Inc. New York, USA



GWP QUOTA SYSTEM IN THE EUROPEAN UNION

The F-Gas Regulation, or "Regulation of the European Parliament and of the Council on fluorinated gases and repealing Regulation (EC) No 842/2006" is an EU legislative instrument which is directly applicable in all EU Member States. The phase-down is a step-by-step approach where the quantities of HFCs expressed in CO2 equivalent that are placed on the market are gradually reduced through the allocation of quotas by the European Commission to producers and importers of bulk HFCs. As a result of the phase-down, HFC consumption will be reduced by 79% 2030. This is an unprecedented reduction and means that industry and users need to make the transition to refrigerants with a lower global warming potential.

The baseline year for HFC consumption has been set as 2015 under this regulation and cutbacks in quotas related to 2015 have already taken place, firstly a 7% reduction in 2016 which was raised to 37% in 2018. A further cutback to 55% of the baseline year will take effect in January 2021. Not surprisingly shortage and high prices have been the result which have led to extensive quantities of illegal imports, thereby threatening the phase down of HFCs in the EU.

The introduction of RS-53 (R470A) aims to help alleviate the shortfall between what is available under F Gas and demand in the market by in effect enabling over 2 tonnes of RS-53 (R470A) to be made available to users for every 1 tonne of R-410A. Crucially, RS-53 (R470A) is non-flammable and therefore can be used in place of R-410A in existing equipment and installations, which of course is not possible in the case of R32 which is flammable and so only suitable for use in new equipment where regulations permit.



The planned cutbacks in 2021 and continued thereafter until a ceiling 21% of the baseline year is permitted in 2030 will significantly accentuate the shortage of refrigerants and/or force users to purchase new equipment in the absence of innovations on the supply side. RS-53 (R470A) should help to alleviate this problem with its much lower GWP compared to R-410A. RS-53 (R470A) has been specifically designed to mitigate these changes to the refrigerant user by reducing the direct GWP of the refrigerant while not compromising its energy efficiency and technical properties as a suitable Drop-in replacement for R-410A.

For more information visit: www.lowgwpref.com / www.replacementforr22.com / service@comstarproducts.com 1-800-328-0142 / www.comstarproducts.com / ComStar International Inc. New York, USA



APPLICATIONS

RS-53 (R470A) has been developed to replace R-410A in existing installations, although it can also be used in new equipment. The problem has been to find a refrigerant which is non-flammable but also with similar properties so that it can easily replace R-410A in practice and at low cost. In the European Union one of the direct effects of the F Gas regulations has been to restrict the availability of R-410A. But now the availability of lower GWP RS-53 (R470A) enables users to avoid the cost of purchasing new equipment, since it significantly increases the refrigerant volume, available under F Gas, for servicing existing systems. RS-53 (R470A) has similar cooling capacity, energy efficiency, discharge pressure, discharge temperature and mass flow as R-410A and consequently an excellent choice to replace R-410A.

Applications for RS-53 (R470A) include but are not restricted to commercial and residential air conditioning, splits, commercial & industrial refrigeration, transport refrigeration, chillers, heat pumps and others. Because the mass flow of RS-53 (R470A) is similar to R-410A, RS-53 (R470A) can be used in systems both with a capillary, fixed orifice or variable expansion devices

LUBRICANTS

RS-53 (R470A) is suitable for use with the same lubricants that are found in R-410A systems, avoiding the need to change the oil when retrofitting to RS-53 (R470A).

SAFETY

RS-53 (R470A) is non-flammable as per ASHRAE Standard 34 based on annex of ASTM A681. The components of RS-53 (R470A) have been subjected to toxicity tests carried out by the Alternative Fluorocarbons Environmental Acceptability Study (AFEAS), and have been declared to be of low toxicity.

SERVICE

Because RS-53 (R470A) is a blend, it should be charged into the system in the liquid as opposed to vapor form. There is no need to make any hardware changes when converting from R410A to RS-53 (R470A) which can be used with expansion devices having a fixed orifice or adjustable setting.



RS-53 (R470A) PHYSICAL PROPERTIES

	RS-53 Physical Properties		RS-532	R-410A2
Notes: 1. Bubble Point. 2. RS-53 refrigerant properties obtained from NIST's REFPROP v10 program. 3. Difference between bubble point liquid enthalpy and dew point vapor enthalpy at 1 atm.	Molecular Mass		84.43	72.6
	Boiling Point (1atm) 1	°C	-62.5	-51.4
		°F	-80.4	-60.5
	Surface Tension (25°C) 1	N/M	0.00623	0.00521
	Critical Temperature	°C	88.7	71.3
		°F	191.7	160.4
	Critical Pressure	bara	55.91	49.00
		psia	810.9	710.6
	Liquid Density at 25 °C 1	kg/m3	1101	1059
	Density of Saturated Vapor at 25°C 1	kg/m3	61.47	64.87
	Latent Heat of Vaporisation at boiling point 3	kJ/kg	268.5	273
	Heat capacity constant volume Cv (25°C & 1bara)	kJ/kg.K	0.749	0.7000
	Vapor Pressure at 25°C 1	bara	18.40	16.57
		psia	267.3	240.4
	Heat capacity constant pressure Cp (25°C & 1bara)	kJ/kg.K	0.854	0.823
	Cp/Cv (25°C & 1 bara)		1.141	1.1755
	Vapor Viscosity (25°C & 1 bara)	сP	0.0130	0.0133
	Liquid Viscosity (25°C) 1	сP	0.139	0.118
	Liquid Thermal Conductivity (25°C)	W/m.K	0.0846	0.0892
	Specific Heat of Liquid at 25°C 1	kJ/kg.K	1.58	1.71
	Ozone Depletion Potential	ODP	0	0
	Global Warming Potential (GWP) AR5	GWP	909	1920
	Flammability Limit in Air (1 atm)	vol%	None	None
	Inhalation Exposure (8 hr Day & 40 hi Week)	ppm	1000	1000

RS-53 (R470A) PRESSURE ENTHALPY CHART

Key Saturation Line Isotherm Isochore Isentrope Quality



5/5

Enthalpy (kJ/kg)

For more information visit: www.lowgwpref.com / www.replacementforr22.com / service@comstarproducts.com 1-800-328-0142 / www.comstarproducts.com / ComStar International Inc. New York, USA